



CERTIFICATE OF COMPLIANCE

Company:

Date:

City:

PRODUCTS & MATERIAL

US Pipe Mexico manufactures Ductile Iron and Gray Iron AWWA C110 Flanged Fittings for both Waterworks and Industrial applications and conforms fully to all required industry standards. US Pipe Mexico also produces C153 Mechanical Joint Fittings under the US Pipe - Metalfit label in full compliance with those standards as well. The production facility is located Pesquería, N.L. Mexico. We are a North American Free Trade Agreement producer.

We hereby certify that all materials furnished by US Pipe Mexico are manufactured and tested in accordance with the following standards, and meet or exceed the requirements and recommendations therein.

- Cast Iron Flanged Fittings.....ANSI B16.1, Class 125 & Class 250
- Cast Iron Flanged Fittings.....ANSI / AWWA C110 / A21.10, Class 125
- Cast Iron Flanged Fittings.....ASTM A 48, minimum tensile 31,000 psi
- Cast Iron FL Water Working Pressure.....2" through 12" - 250 psi
14" through 48" - 150 psi
- Ductile Iron Flanged Fittings.....ANSI / AWWA C110 / A21.10 ANSI B16.1, Class 125
- Ductile Iron Flanged Fittings.....ASTM A 536 for Mechanical Properties
Minimum Tensile Strength 70,000 psi
Minimum Yield Strength 50,000 psi
Minimum Elongation 5%
- Ductile Iron FL Water Working Pressure.....2" through 48" – 250 psi
Per ANSI / AWWA C111 / A21 / 11, states that 3" through 24"
may be rated to 350 psi with the use of "special" gaskets
- Ductile Iron Compact Mech. Joint Fittings.....ANSI / AWWA C153 / A21.53
- DI Compact MJ Water Working Pressure.....3" through 24" - 350 psi
30" through 48" - 250 psi unless otherwise noted
- Cement Mortar Lining.....ANSI / AWWA C104 / A21.4
- Protecto 401 Lining.....In accordance with the "Licensed Applicator Agreement"
- Standard Coatings and Linings.....ANSI / NSF 61

Joe Gobeille
Vice President

2023 Saint Louis Ave
Bessemer, AL 35020

Byron Sanders
Project Services Manager
205-417-841Main
864-616-6572 Cell
bsanders@uspipe.com